

Printing date 13.04.2016 Revision: 13.04.2016

SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- · Trade name: Endura Silikonlu Dış Cephe Boyası
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 No further relevant information available.
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Maykem Yapı ve Kimya San. Tic. LTD. ŞTİ.

Mescit Mah. Demokrasi Cad. Birmes San. Sit. B/10 Blok No:15

Tuzla/Istanbul 34947 Tel: 0(216) 394 2610 pbx www.maykem.com



- · Further information obtainable from: KGR Kimyasal Güvenlik Riskleri Dan. Hiz. ve Tic. LTD. ŞTİ.
- 1.4 Emergency telephone number: During normal opening times: 0(216) 394 2610 pbx

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

5-chloro-2-methyl-2H-isothiazol-3-one

· Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 2)



Printing date 13.04.2016 Revision: 13.04.2016

Trade name: Endura Silikonlu Dış Cephe Boyası

· vPvB: Not applicable.

(Contd. of page 1)

<0.1%

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

 Dangerous 	components:
-------------------------------	-------------

CAS: 26172-55-4 5-c

5-chloro-2-methyl-2H-isothiazol-3-one

EINECS: 247-500-7 🔗 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331;

Skin Corr. 1B, H314; Aquatic Acute 1, H400; Aquatic Chronic 1,

H410; (1) Skin Sens. 1, H317

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out into the fresh air.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water.

Seek medical treatment.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture Do not inhale combustion products.
- 5.3 Advice for firefighters
- · Protective equipment: Wear protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Send for recovery or disposal in suitable receptacles.

(Contd. on page 3)



Printing date 13.04.2016 Revision: 13.04.2016

Trade name: Endura Silikonlu Dış Cephe Boyası

(Contd. of page 2)

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Store in cool, dry place in tightly closed receptacles.

- Information about fire and explosion protection: No special measures required.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Notrequired.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated

clothing Wash hands before breaks and at the end of

work. Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Keep away from foodstuffs, beverages and feed.

Ensure that eye wash stations are available at the work place.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 4)



Printing date 13.04.2016 Revision: 13.04.2016

Trade name: Endura Silikonlu Dış Cephe Boyası

· Material of gloves

(Contd. of page 3)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and ch	emical properties
.1 Information on basic physical a	and chemical properties
General Information	. ,
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour: Odour threshold:	Characteristic Not determined.
oH-value:	Not determined.
	Not determined.
Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not applicable.
gnition temperature:	постарриодии.
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
/apour pressure:	Not determined.
Density at 20 °C:	1,70 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient (n-octanol/wat	ter): Not determined.
/iscosity:	
Dynamic at 25 °C:	130 KU
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	0,0 %
VOC (EC)	0,00 % No further relevant information available.



Printing date 13.04.2016 Revision: 13.04.2016

Trade name: Endura Silikonlu Dış Cephe Boyası

(Contd. of page 4)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
26172-55-4 5-chloro-2-methyl-2H-isothiazol-3-one			
Oral	LI	D50	100 mg/kg (ATE)
Dern	nal Ll	D50	300 mg/kg (ATE)
Inhal	lative L0	C50/4 h	3 mg/l (ATE)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

El



Printing date 13.04.2016 Revision: 13.04.2016

Trade name: Endura Silikonlu Dış Cephe Boyası

(Contd. of page 5)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	tion
· 14.1 UN-Number · ADR, IMDG, IATA	Void
· 14.2 UN proper shipping name · ADR, IMDG, IATA	Void
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA · Class	Void
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Transport in bulk according to An of Marpol and the IBC Code	nex II Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

5-chloro-2-methyl-2H-isothiazol-3-one

· Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 7)



Printing date 13.04.2016 Revision: 13.04.2016

Trade name: Endura Silikonlu Dış Cephe Boyası

(Contd. of page 6)

Wear protective gloves/protective clothing/eye protection/face protection. P280

P321 Specific treatment (see on this label). P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Department issuing SDS:



KGR-Kimyasal Güvenlik Riskleri Danışmanlık Hiz.veTic.Ltd.ŞTİ.

Velibaba Mah. İstanbul Cad. No:16-5 D:16 Pendik/ISTANBUL

Tel: +90 535 7247114

www.kgr.com.tr info@kgr.com.tr

· Contact: Caner MASMANACI (Turkish standards institute certificate no: GBF-A-0-2226)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1